

WaterGroup®

WG NRV (Non-Regenerating Valve) Whole House Carbon Filter

Economical Reduction of Chlorine and Other Bad Taste & Odors

Once water arrives safely at your home there is no further need for disinfectants. In fact they are undesirable! Disinfectants cause taste and bad odor, dry skin, damage plumbing, and can produce potentially harmful by-products.



**97% Chlorine
Removal!
Over 1,100,000
gallons**



Certified by IAPMO R&T
to NSF/ANSI 42 for
Chlorine Reduction



NRVTO-150



Economical Reduction of Chlorine, Chloramines and other bad taste & Odors.

Features:

- ➔ Economical whole-house carbon filtration solution for reducing chlorine and other bad tastes and odors. TOCK models reduce chlorine, chloramines plus hydrogen sulfide (H₂S) caused by sulphate reducing bacteria common in warmer climates.
- ➔ Factory installed one-piece bypass
- ➔ Time saving quick connect fittings (90° ¾" NPT elbows and 1" straight NPT) included for faster, easier installation. Optional quick connect SharkBite® fittings also available.
- ➔ Five year warranty on distribution head
- ➔ Ten Year warranty on NSF certified tank

90° ¾" NPT Elbows



Economical non-back-washing distribution head with convenient quick connect fittings

1" Straight NPT



Specifications	NRV TO-100 15054073	NRV TO-150 15054074	NRV TOK-100 15054075	NRV TOK-150 15054076
Peak Flow Rates	4.0 gpm	5.0 gpm	4.0 gpm	5.0 gpm
Filter Media Volume - Cubic Feet	1.0 ft ³	1.5 ft ³	1.0 ft ³	1.5 ft ³
Filter Tank Size (inches)	9 x 48	10 x 54	9 x 48	10 x 54
Media Type	Coconut Carbon	Coconut Carbon	Coconut Carbon With KDF Distributor	Coconut Carbon With KDF Distributor
Media Loaded	Yes	Yes	Yes	Yes
KDF Protector	No	No	Yes	Yes
Tank Jacket	No	No	No	No
Shipping Weight	60 lbs	78 lbs	60 lbs	78 lbs
Plumbing Connections	Includes 3/4" 90° Elbows & 1" Straight NPT. Bypass Included			
Electrical Requirements	None			
Water Temperature	Min 39 - Max. 100 degrees Fahrenheit			
Water Pressure	Max. 125 psi			

The life expectancy of the carbon media bed in these units will be reduced as compared to a back washing style carbon filter. The actual media bed life will vary depending on water consumption, chlorine/chloramines concentration and flow rate. Exceeding the peak flow rate listed above will drastically reduce the life expectancy of the carbon media.



Certified by IAPMO R&T
to NSF/ANSI 42 for
Chlorine Reduction



Toll Free: 1-877-288-9888
www.watergroup.com

Regina, SK • Cambridge, ON • Whitestown, IN
Phoenix, AZ • Houston, TX • Guadalajara, MX

Your Local Plumbing Professional



80156017 2023-05-25
Download only